

## PATTERN 7752

### PATTERN PIECES:

<b>DOG COAT:</b>		D 15 Belt 1x
A 1 Coat 2x		D 16 Chest Strap 1x
A 2 Collar 1x		D 17 Flap 1x
A 3 Belt 1x		D 18 Pocket 1x
A B 4 Loop 1x	E 19 Back 1x	
B 5 Coat 2x	E 20 Front 2x	
B 6 Pocket 2x	E 21 Sleeve 2x	
B 7 Fringe 1x	E 22 Frill I 1x	
C 8 Coat 1x	E 23 Frill II 1x	
C 9 Collar 2x	E 24 Frill III 1x	
C 10 Belt 1x	E 25 Sleeve Frill 2x	
C 11 Strip 2x	E 26 Neckband 1x	
C DE 12 Loop 1x	E 27 Facing 2x	
D 13 Coat 1x	F 28 Neckerchief 1x	
D 14 Collar 1x		

THE CUTTING LAYOUTS ARE ON THE PATTERN SHEET

### PREPARING PATTERN PIECES

#### A-F

Cut out the pattern pieces for your chosen project in the required size (S, M, L) from the pattern sheet.

See the size chart to determine the required pattern size. Adjust the pattern pieces, if necessary, by adding or subtracting the number of inches that your dog's measurements differ from the measurements given in the chart.

### CUTTING OUT

The cutting diagrams on the pattern sheet show how the pattern pieces should be placed on the fabric.

#### A-F

**SEAM AND HEM ALLOWANCES** must be added to the pattern pieces:

$\frac{5}{8}$ " (1.5 cm) at all seams and edges.

See each set of project instructions for further details.

For a single layer of fabric, the pattern pieces are pinned to the right side. For double layers of fabric, the right sides are facing and the pattern pieces are pinned to the wrong side.

#### FABRIC I, II and Lining

Follow the cutting diagrams to cut the pieces of different fabrics.

➔ See cutting diagrams on pattern sheet.

See each the instructions for each project for further details on cutting out the pattern pieces.

### TRANSFERRING PATTERN MARKINGS

Mark important pattern piece lines and markings on the pattern pieces with BURDA dressmaker's carbon paper and a tracing wheel (see instructions included with the pack) or with chalk.

Use basting thread to transfer important lines to the right side of the fabric.

### SEWING

#### A - Dog's Coat with Collar

##### Notions:

3 hammer-on snap fasteners; pre-folded bias tape,  $1\frac{1}{2}$ " (4 cm) wide:

$2\frac{1}{2}$  -  $3\frac{1}{4}$  -  $4\frac{1}{4}$  yds (2.15 - 2.90 - 3.75 m); touch fastening tape,  $\frac{3}{8}$ " (2 cm)

wide: 8" - 10" - 12" (20 - 25 - 30 cm)

##### Cutting out:

Follow the cutting diagram to cut pieces 1 to 4 of two fabrics (vinyl-coated fabric, cotton fabric). Do **not** include allowance at edges to bind (edges with scissors symbol).

#### Coat / Outside

① Lay coat pieces right sides together. Stitch **center back seam**. Press allowances open. Topstitch close to each side of seam.

② Stitch **darts** at side edges toward points of darts. Press darts toward back edge.

③ Lay collar pieces wrong sides facing, pin edges together. Lay bias tape around front and upper edges of collar, folding bias tape at corners. Pin bias tape in place and stitch close to edge, binding edges.

④ Baste collar on edge of neckline (seam number 1); front edges meet at center front.

**Double the coat:** Stitch center back seam and darts on fabric for inside (= lining) as for outside of coat.

⑤ Pin lining right sides together with coat. Baste and stitch front edges and neck edges together, catching collar in between. Trim allowances, clip curves. Turn coat. Baste edges, press and topstitch close to edges. Bind outer edges with bias tape as described and illustrated in step 3, beginning and ending in front. Turn in ends of bias tape.

⑥ **Loop:** Lay pieces right sides facing. Stitch long edges together. Trim allowances.

Use a safety pin as a bodkin to turn piece. Baste edges, press and topstitch close to edges.

Pin loop under end of coat from each marking and stitch exactly in stitching line of binding (6a).

⑦ **Belt:** Press allowance at narrow edges of both pieces to inside. Pin pieces wrong sides together. Bind long edges with bias tape. Stitch narrow edges together. Stitch four pieces of touch fastening tape onto ends as marked (7a). Stitch matching pieces of other half of fastening tape on inside of coat as marked. Attach belt with fastening tape.

Attach **3 top halves of snap fasteners** at x on one front edge. Attach **bottom halves of snaps** along center front of other edge.

#### B - Dog's Coat with Fringe

##### Notions:

2 hammer-on snap fasteners; velvet ribbon,  $\frac{3}{8}$ " (1.5 cm) wide:

$1\frac{1}{4}$  -  $2\frac{1}{2}$  -  $3\frac{1}{2}$  yds (1.60 - 2.40 - 3.20 m)

##### Cutting out:

Follow the cutting diagram to cut pieces 4 to 7 of **top fabric**. Lengthen piece 7; e. g. trace piece on the fabric as often as required to obtain the given length and cut without allowance. Cut pieces 5 and 6 of **lining**.

#### Coat / Center Back Seam

⑧ Lay pieces right sides together. Stitch center seam on fabric and lining. **Important:** Leave an opening in lining for turning. Secure ends of stitching. **Illustration shows lining.**

Press allowances open.

#### Pockets

⑨ Cut two pieces from the strip for the fringe the width of the pockets and baste on the pockets so that the top half lies on the marked band. Stitch band. Draw out fabric threads to create fringe below band (9a).

⑩ Pin pocket lining pieces right sides together with fabric pockets. Stitch edges together, leaving an opening for turning. Secure ends of stitching. Trim allowances, clip curves, trim corners diagonally.

Turn pockets. Baste edges, press. Baste pockets on coat at placement lines and stitch pockets close to edges, closing opening in seam (10a).

⑪ Pin lining right sides together with coat, baste and stitch all edges together. Trim allowances, trim corners diagonally, clip curves.

Turn coat. Baste edges, press. Stitch up opening in seam of lining.

⑫ Baste fringe strip on all edges of coat as illustrated with wrong side facing right side, make folds at corners. Half of the strip overhangs.

⑬ Baste velvet ribbon on all edges, make folds at corners. Stitch ribbon close to edges. Draw out fabric threads from fringe strip to create fringe up to the velvet ribbon.

#### Loop

⑭ Trim allowance at lengthwise edges of fabric strip and press to center. Baste on velvet ribbon wrong sides facing and stitch closely round edges.

Pin loop under back edge of coat between markings and stitch exactly in stitching line of velvet ribbon (14a).

Attach **2 top halves of snap fasteners** at x on one front edge. Attach bottom halves of snaps along center front of other edge.

#### C - Dog's Coat of Imitation Leather with Backing

##### Notions: 5 hammer-on snap fasteners

**Cutting out:** Follow the cutting diagram to cut pieces 8 to 12.

#### Coat

⑮ Baste collar **wrong sides together** with neck edge (seam number 2) and stitch, **not** stitching across slit for neckband. Secure ends of stitching. Press allowances open.

⑯ Cut off allowance at front and upper edges of other collar piece. Stitch collar right sides together with collar already stitched. Pin collar. Stitch close to lower edge. Clip slit. Stitch edges of slit together.

⑰ Turn allowance at all outer edges outward as illustrated, pin and stitch closely.

## Pattern 7752

### C

- 18** Lay fabric strip (piece 11) around armhole edges, pin and stitch in place close to edges of strip.
- 19** Stitch side seams **wrong sides together** (seam number 3). Press allowances open and stitch close to edges.
- 20** **Loop:** Cut off allowance at lengthwise edges. Fold strip in half lengthwise, wrong side facing in. Stitch edges together. Pin loop under edge of coat between markings and stitch exactly in stitching line of allowance.
- 21** **Belt:** Turn allowance at all edges outward, stitch close to edges. Attach **bottom halves of snap fasteners** at x. Attach **top halves of snaps** to coat. Attach **3 top halves of snap fasteners** at x on one front edge. Attach bottom halves of snaps along center front of other edge.

### D - Dog's Coat Doubled, Edges Bound with Braid

**Notions:** 1" (2.5 cm) braid: 2¼ - 3½ - 4¼ yds (2.00 - 2.80 - 3.80 m); touch fastening tape, ¾" (2 cm) wide: 8" - 12" - 16" (20 - 30 - 40 cm); 1 hammer-on snap fastener.

**Cutting out:** Follow the cutting diagram to cut pieces 12 to 18 of two fabrics (fulled fabric, cotton fabric).

#### Coat / Outside

Stitch **darts** at side edges toward points of darts. Press darts toward back edge (see illustration 2).

Lay **collar pieces** wrong sides facing. Pin edges together. Bind edges with braid as described and illustrated in step 26.

- 22** Baste collar on neck edge (seam number 4); front edges meet at center front, fulled fabrics are facing.

**Double coat:** Stitch darts on inside fabric in the same manner as on outside fabric.

- 23** Pin coat pieces right sides together. Baste and stitch neck edges together, catching collar in between. Trim allowances, clip curves. Turn coat. Baste open edges together. Bind outer edges with braid as described and illustrated in step 26, turning in ends of braid.

- 24** **Loop:** Fold piece lengthwise, right side facing in. Stitch long edges together. Trim allowances. Use a safety pin as a bodkin to turn loop piece. Pin loop under edge of coat between markings and stitch exactly in stitching line of braid. Separate the **fastening tape** and trim each piece to a width of ¾" (1 cm). Stitch two pieces of fastening tape under side edges of coat as marked and on piece each under front edges.

- 25** **Pocket:** Pin pieces right sides facing, stitch upper edges together. Turn pocket. Baste edges, press. Bind side and lower edges with braid, turning in ends of braid. Baste pocket on coat at placement line and stitch in stitching line of braid.

- 26** **Flap:** Pin pieces wrong sides together. Bind side edges and lower edges with braid. Trim open edges to ¼" (0.7 cm) and neaten together. Stitch flap right sides together with joining line. Secure ends of stitching (26a). Press flap down. Topstitch upper edge ⅜" (0.5 cm) wide (26b). Attach **top half of snap** on flap, **bottom half of snap** on pocket to match.

#### Belt / Chest Strip

- 27** Pin pieces for belt right sides facing. Baste and stitch together, leaving an opening between markings. Secure ends of stitching. Trim allowances, trim corners diagonally. Turn piece. Baste edges, press.
- 28** Pin pieces for the chest strap right sides facing. Stitch edges together, leaving edge with seam number 5 open. Trim allowances, trim corners diagonally. Turn piece. Baste edges, press and topstitch ¼" (0.7 cm) wide.
- 29** Insert chest strap into opening in seam of belt (seam number 5). Stitch belt close to edge. Topstitch round all edges ¼" (0.7 cm) wide. Stitch **2 pieces of fastening tape each** on side edges of belt as marked and one piece on front end of chest strap. belt am coat festkletten.

### E - Dog's Coat with Frills

**Notions:** 8 hammer-on snap fasteners; rib knit fabric for neckband

**Cutting out:** Follow the cutting diagram to cut pieces 12, 19, 20 and 21 of coat fabric, cut pieces 22 to 25 and 27 of print fabric, cut piece 26 of rib knit fabric.

### Shoulder Seams and Side Seams

- 30** Lay front right sides together with back. Stitch shoulder seams (seam number 6) and side seams (seam number 8) stitch. Trim allowances and press open. Topstitch close to each side of seams.
- 31** Fold **neckband** lengthwise, right side facing in. Stitch front edges together. Trim allowances. Turn neckband. Pin open edges together.
- 32** Baste neckband right sides together with neck edge (seam number 7). Neaten facing and baste right sides together with front and lower edges and neckline (seam number 12). Stitch facing and collar. Trim allowances, trim corners diagonally. Neaten allowances of neckband joining seam together. Neaten allowances of side and back coat edges.
- 33** Baste facing and go on to baste allowances of side and back coat edges to inside, press. Topstitch round all edges ¼" (0.7 cm) wide.
- 34** **Sleeve with Frill:** Press allowance at lower edge of frill to inside. Topstitch fold edge at a close zigzag setting. Trim surplus allowance close to stitching.
- 35** To gather frill, stitch two closely spaced lines of machine basting (longest stitch setting) along upper edge. Pull bobbin threads to gather to fit sleeve. Knot ends of thread. Distribute gathering evenly. Stitch frill right sides together with lower edge of sleeve (seam number 9). Trim allowances, neaten together and press into sleeves (35a). Fold sleeves lengthwise, stitch **sleeve seams** (seam number 10). Press allowances open.
- 36** Pin sleeve into armhole, right sides facing.  
➔ Match markings 11 on sleeve and front. Match sleeve and side seams. Match marking at top of sleeve with shoulder seam. Baste and stitch sleeve from sleeve side. Trim seam allowances, neaten together.

**Frills:** Neaten allowance at side and lower edges of all frill pieces as described and illustrated in step 34. Gather each upper edge as described and illustrated in step 35 to fit length of joining edge on back piece.

- 37** Stitch frills in place one after the other right sides together with joining lines. Press frills down over joining seam (37a). Construct **loop** and stitch under edge as described and illustrated in step 24. Attach **snap fasteners** on front edges as marked.

### F - Neckerchief

**Notions:** 3" (7 cm) of ⅝" (1 cm) wide touch fastening tape; pre-folded bias tape, 1¼" (3 cm) wide: 1½ - 1¾ - 2¼ yds (1.30 - 1.65 - 2.00 m).

- 38** Bind all edges of neckerchief with bias tape. Stitch **fastening tape** on and under edges of neckerchief as marked.