

## PATTERN 7753

### PATTERN PIECES:

**M: 12" - 14" (30 cm – 35 cm)**

#### JACKET

A 1 Front 2x  
A 2 Back 1x  
A 3 Sleeve 2x  
A 4 Pocket 2x  
A 5 Fringe / Neckline 1x

#### HOODED JACKET / BOLERO

B 6 Front 2x  
B 7 Back 1x  
B C 8 Sleeve 2x  
B 9 Hood 2x  
B 10 Pocket 2x  
C 11 Front 2x  
C 12 Back 1x  
C 13 Collar 2x

#### SHIRT / BLOUSE

D E 14 Front 2x  
D E 15 Back 1x  
D E 16 Collar 2x  
D 17 Sleeve 2x  
E 18 Sleeve 2x

#### VEST

F 19 Front 2x  
F 20 Back 1x

#### SKIRT/ BIBBED SKIRT

G H 21 Front Skirt Panel 2x  
G H 22 Back Skirt Panel 2x  
G 23 Waistband 1x  
H 24 Bib 2x  
H 25 Waistband 2x  
H 26 Pocket 1x  
H 27 Strap 2x  
H 28 Frill 2x

#### PANTS

J 29 Front Pant Piece 2x  
J 30 Back Pant Piece 2x

#### DRESS

K 31 Front 1x  
K 32 Back 2x  
K 33 Sleeve 2x  
K 34 Skirt Panel 1x

#### CAP

L 35 Cap 1x

**L: 16" - 18" (40 cm – 45 cm)**

#### JACKET

A 36 Front 2x  
A 37 Back 1x  
A 38 Sleeve 2x  
A 39 Pocket 2x  
A 40 Fringe / Neckline 1x

#### HOODED JACKET / BOLERO

B 41 Front 2x  
B 42 Back 1x  
B C 43 Sleeve 2x  
B 44 Hood 2x  
B 45 Pocket 2x  
C 46 Front 2x  
C 47 Back 1x  
C 48 Collar 2x

#### SHIRT / BLOUSE

D E 49 Front 2x  
D E 50 Back 1x  
D E 51 Collar 2x  
D 52 Sleeve 2x  
E 53 Sleeve 2x

#### VEST

F 54 Front 2x  
F 55 Back 1x

#### SKIRT/ BIBBED SKIRT

G H 56 Front Skirt Panel 2x  
G H 57 Back Skirt Panel 2x  
G 58 Waistband 1x  
H 59 Bib 2x  
H 60 Waistband 2x  
H 61 Pocket 1x  
H 62 Strap 2x  
H 63 Frill 2x

#### PANTS

J 64 Front Pant Piece 2x  
J 65 Back Pant Piece 2x

#### DRESS

K 66 Front 1x  
K 67 Back 2x  
K 68 Sleeve 2x  
K 69 Skirt Panel 1x

#### CAP

L 70 Cap 1x

THE CUTTING LAYOUTS ARE ON THE PATTERN SHEET

### PREPARING PATTERN PIECES

#### A-K

Cut out the pattern pieces required for your chosen project in the correct size (M, L) from the table on the pattern sheet.

### CUTTING OUT

**FOLD** (– – –) means: here is the center of a pattern piece but in no case a cut edge or a seam. The piece should be cut double, with the fold line forming the center line.

Pattern pieces that are outlined with a broken line in the cutting diagrams are to be placed face down on the fabric.

The cutting diagrams on the pattern sheet show how the pattern pieces should be placed on the fabric.

**F** Cut pieces of fabric and lining.

**K** Cut the skirt panel (piece 34) of dress fabric I and organza II.

➔ See cutting diagrams on pattern sheet.

#### A-L

Seam and hem allowances are included on the pattern pieces:

All pattern pieces include the required seam and hem allowances.

Cut out the fabric pieces directly along the edges of the paper pattern pieces

For a single layer of fabric, the pattern pieces are pinned to the right side. For double layers of fabric, the right sides are facing and the pattern pieces are pinned to the wrong side. The pattern pieces that are shown in the cutting diagram extending over the fold of the fabric should be cut last from a single layer of fabric.

### SEWING

The dashed lines (– – –) on the pattern pieces indicate where the pieces are to be stitched together. Match same seam numbers.

When sewing, right sides of fabric are facing.

#### A JACKET

Lay front pieces right sides together with back. Stitch **shoulder seams** (seam number 1).

① Neaten **pockets** round all edges. Baste allowances at upper edge of pocket to wrong side. Stitch TRIM onto upper edge of pocket. Baste remaining allowances to wrong side, press. Baste pockets on fronts at placement lines and stitch close to edges (1a).

#### Stitch on Sleeves

② Pin sleeves right sides together with armhole edges. Match markings 2 on sleeve and front. Match marking at sleeve cap with shoulder seam. Baste and stitch sleeve from sleeve side.

Trim seam allowances, neaten together and press toward sleeves.

#### Fringe / Lower Edge of Sleeve

③ Zigzag stitch ¼" (0.7 cm) next to lower edge of sleeve. Draw out fabric threads to fringe the edge up to zigzag stitching. Stitch TRIM on along zigzag stitching.

④ Lay fronts right sides together with back, Fold sleeves lengthwise. Baste **side seams and sleeve seams** (seam number 3). Match ends of sleeve inset seams. Stitch, not stitching over seam allowances at lower edge of jacket. Secure ends of stitching.

Zigzag stitch front and lower edges of jacket and fringe these edges as described and illustrated in step 3.

#### Fringe / Neckline

Clip allowances at neckline, turn to inside and baste.

Zigzag stitch along middle of strip for fringe. Fringe one edge, neaten the other.

⑤ Baste strip under edge of neckline so that fringe is visible. Stitch fringe strip in place close to edge.

Stitch TRIM on front and lower edges of jacket and on edge of neckline.

Sew **BUTTONS** on a x-markings on both fronts and on pockets. Join buttons at neckline with a small chain.

#### B HOODED JACKET

Lay fronts right sides together with back. Stitch **shoulder seams** (seam number 4).

Stitch **sleeves** (seam number 5) as described and illustrated in step 2.

⑥ **Hem / Sleeve hem:** Lay facing at lower edges of sleeves and on front and back pieces outward. Baste. Stitch edges at a zigzag setting.

Stitch **side seams and sleeve seams** (seam number 6) as described and illustrated in step 4. Secure ends of stitching.

⑦ **Hood:** Stitch darts on hood pieces toward points of darts. Lay darts toward center back.

Stitch **facing** at front edge of hood as described and illustrated in step 6.

⑧ Lay hood pieces right sides together. Stitch center seam. Spread seam allowances apart.

⑨ Stitch hood right sides together with neck edge (seam number 7), matching darts with shoulder seams.

⑩ Baste **zipper** exposed under front edges. Turn in any surplus length of zipper at the top and trim off. Stitch zipper with the zipper foot of your sewing machine.

#### Pockets

⑪ Turn facing to inside on fold line, baste at the sides. Edgestitch pockets on fronts at placement lines.

#### C BOLERO

Lay fronts right sides together with back piece. Stitch **shoulder seams** (seam number 8).

Stitch **sleeves** (seam number 5) as described and illustrated in step 2.

Lay hem at **lower edges of sleeves** to inside, baste. Stitch hem close to edge.

Stitch **side seams and sleeve seams** (seam number 6) as described and illustrated in step 4. Secure ends of stitching.

Turn allowances at **front and lower edges** to inside, stitch close to edges.

⑫ **Collar:** Lay collar pieces right sides facing. Stitch edges together as illustrated.

Turn collar, baste edges. Baste open edges together.

⑬ Stitch collar right sides together with neck edge (seam number 9). Press seam allowances onto front and back. Topstitch close to joining seam, catching seam allowances.

⑭ Work a thread loop at right front edge between markings. Sew **BUTTON** on left front edge to match.

## Pattern 7753

### DE SHIRT / BLOUSE

Lay fronts right sides together with back. Stitch **shoulder seams** (seam number 10).

**Stitch sleeves** (seam number 11) as described and illustrated in step 2.

Neaten **sleeve hem**, press to inside. Stitch narrow hem.

**Stitch side seams and sleeve seams** (seam number 12) as described and illustrated in step 4. Secure ends of stitching.

Stitch **collar** as described and illustrated in step 12 stitch. Trim seam allowances at corners diagonally.

Turn collar, baste edges. Baste open edges together.

**15** Baste collar right sides together with neck edge, matching centers (seam number 13). Lay front self-facing outward on fold line and baste on neck edge over collar. Stitch collar and facing.

Turn facing to inside. Press allowances onto front and back. Topstitch close to joining seam, catching allowances (15a).

**16** **Fastening:** Cut a strip of touch fastening tape about  $\frac{3}{8}$ " (1 cm) wide and about  $4\frac{1}{2}$ " (12 cm) long. Separate the tape. Baste soft half under right front edge, matching centers. Baste rough half on left front edge to match. Edgestitch fastening tape in place.

Sew **BUTTONS** on right front edge at x-markings.

Press **hem** to inside, stitch narrow hem.

### F VEST

Stitch **side seams** on top fabric and lining (seam number 14).

**17** **Double the vest:** Lay vests of top fabric and lining right sides facing. Stitch outer edges and edges of armholes together. Leave shoulder seams open. Leave an opening of about  $1\frac{1}{2}$ " (4 cm) at lower edge for turning. Clip allowances.

Turn vest through opening in seam. Baste edges, topstitch close to edges.

Lay fronts right sides together with back. Stitch **shoulder seams** (seam number 15). Neaten allowances and press open.

Attach **EYELETS** at bottom of armhole as marked.

Attach **SNAP FASTENERS** at x-markings in center front: top halves of snaps on the right and bottom halves of snaps on the left.

### GH SKIRT/ BIBBED SKIRT

#### Front and Back Center Seam /Slit

Lay front skirt panels right sides together. Stitch center front seam.

**18** Lay back skirt panels right sides together. Baste center seam, stitch seam from lower edges to slit mark.

Neaten seam allowances and press onto left back skirt panel.

Lay front and back skirt panels right sides together. Stitch **side seams** (seam number 16).

### G

**19** **Waistband:** Press allowance at back left end of waistband to inside. Neaten right end. Fold waistband on fold line with wrong side facing in. Baste long open edges together.

Stitch waistband right sides together with upper edge of skirt. Neaten allowances together and press down (19a).

**20** Insert elastic into waistband to fit waist, stitch ends together.

**21** Cut a strip of **touch fastening tape** about  $\frac{1}{4}$ " (0.7 cm) wide and about 2" (5 cm) long. Separate the tape. Stitch soft half of tape under left back opening edge. Stitch rough half of tape on allowance of right edge.

### H Bib

**22** Lay bib pieces right sides facing. Stitch together as illustrated. Clip seam allowances, trim corners diagonally. Turn bib. Topstitch close to edges, baste open edges together.

Construct **pocket** as described and illustrated in step 1, topstitch upper edge  $\frac{3}{8}$ " (0.5 cm) wide. Stitch pocket on bib at placement line.

**23** Stitch waistband pieces right sides together with side edges of bib (seam number 17), edge of bib meets with fold line on waistband.

Press seam allowances onto waistband. Press allowance at left back end of waistband to inside. Fold waistband on fold line, wrong side facing in, baste lower edges together.

Stitch **waistband and bib** as described and illustrated in step 19a.

**24** Insert elastic into waistband pieces. Stitch ends in place.

Stitch on **TOUCH FASTENING TAPE** as described and illustrated in step 21.

**25** Press allowances at long edges and one end of **straps** to inside, fold on fold line. Topstitch close to edges.

Stitch straps under upper edge of waistband with open ends centered on back skirt panels.

Attach **SNAPS** at front ends of straps and on bib.

**Frill:** Lay pieces right sides together, stitch side seams.

**26** Press allowances at lower edge of frill to inside. Topstitch fold edge with close zigzag stitching. Trim surplus allowance close to stitching. Gather upper edge of frill, e.g. stitch two closely spaced lines of machine basting (longest stitch setting). Pull bobbin threads to gather to fit lower edge of skirt. Distribute gathering evenly.

Stitch frill right sides together with lower edge of skirt. Neaten seam allowances together and press onto skirt (26a).

### J PANTS

#### Side Seams and Inside Leg Seams

**27** Lay front pant pieces right sides together with back pant pieces. Stitch side seams (seam number 18) and inside leg seams (seam number 19).

**28** Turn one pant leg right side out. Pull pant legs one over the other right sides facing. Stitch **center seam**, matching inside leg seams. Secure ends of stitching.

#### Upper Edges of Pants / Elastic Casing

**29** Neaten facing, turn in on fold line, baste and press. Topstitch upper edge of pants  $\frac{3}{8}$ " (1.5 cm) wide, leaving an opening to insert elastic. Insert elastic to fit waist. Sew ends together. Sew up opening in seam. Neaten **hem**, baste to inside and stitch.

### K DRESS

Lay fronts right sides together with back. Stitch **shoulder seams** (seam number 20).

**Sleeves:** Baste facing at lower edge of sleeve to inside, press.

**30** Gather upper edge of sleeve between  $\star$ , e.g. stitch two closely spaced lines of machine basting (longest stitch setting). Pull bobbin threads to gather.

#### Lower Edge of Sleeve / Elastic Casing

**31** Cut elastic to fit upper arm plus  $\frac{3}{8}$ " (1.5 cm). Lay elastic on facing as marked, stretch and zigzag stitch in place.

**Stitch sleeve** (seam number 21) as described and illustrated in step 2, distributing fullness evenly.

#### Neckline / Bias Tape

**32** Fold facings outward on fold line, pin at neckline. Fold bias tape in half lengthwise, baste at neckline, ends lie on facing and open edges lie on the allowance. Stitch. Clip allowances.

Turn facing and bias tape to inside, baste edges, topstitch close to edges.

**Stitch side seams and sleeve seams** (seam number 22) as described and illustrated in step 4.

**33** Lay **skirt panels** right sides together. Stitch center back seam from lower edges to slit mark. Press allowances open.

Neaten **hem** as described and illustrated in step 26.

Place skirt of organza over skirt with wrong side facing right side. Gather upper edges to fit edge of top of dress as described and illustrated in step 26a.

**34** Stitch skirt right sides together with top of dress, matching centers (seam number 23). Press allowances onto top of dress. Turn facing to inside.

Stitch on **TOUCH FASTENING TAPE** for back fastening as described and illustrated in step 16. Sew **BUTTONS** on at x-markings. Tie **RIBBON** around waist if desired.

### L CAP

Stitch facing at lower edge as described and illustrated in step 6.

Join cap to a round right side facing in.

**35** Gather upper edge of cap at marking, e.g. stitch two closely spaced lines of machine basting (longest stitch setting). Pull bobbin threads as tightly as possible to gather cap. Conceal ends of thread.